



LS Tractor MT463CPS Power Shuttle Utility Tractor - Loader

[Read More](#)

SKU: LS-MT463CPS

Categories: [LS Tractors](#)

Product Description

LS Tractor MT463CPS Utility Tractor - Loader

Key Features

- MT4 redesigned with new LS Family Look. New hood design allows for improved engine performance and serviceability
- LED Lamps for all models provide better illumination for more efficient work in darker operating conditions
- Larger tire size options which provide better grip and traction with lower ground pressure.
- 15% more space in new cab design than previous model allows for more comfort and convenience in the same footprint. Additionally, the redesigned cab offer improved access to key components for easier diagnosis and routine maintenance
- Improved high back for seat with wider and improved cushion for greater operator comfort
- Enhanced lift height (up to 132.9" in max height mode) and capacity (3,487 lb in max power mode) for front loader (LL5001) with standard self leveling bucket
- Standard 2 sets of remote valves. Adds functionality and improves ease of use by allowing attachment of hydraulically controlled implements without the high, additional costs like others in its class to add the remotes as options.
- Extendable lower links. Category 2 with hitch lift capacity of 4,079 lbs. allows easier attachment of a wide variety of implements.
- Standard 3rd function button on joystick

Specifications

Engine

Type	Vertical Water-Cooled 4 Cycle Diesel Engine
Model (Tier 4)	L4C25-T
Engine HP (Gross)	63

PTO HP	54.1
Rated Speed (RPM)	2,500
Displacement (cu. in)	152.85
Fuel Tank Capacity (gal)	24.3

Drive Train

Transmission Type	Power Shuttle
No. of Speed	F16 X R16
Brakes	Wet, Multi-disc
Steering	Hydrostatic Power Steering

PTO

Type	Independent
Rear, rpm	540, 540E (Standard)

Hydraulic System

Control System	Position / Draft
Implement pump (gpm)	14.5
Steering pump (gpm)	6.6
Total flow (gpm)	21.1
Category, 3 pt hitch	CAT II
Hitch Lift capacity, lbs (Hitch end)	3,483 (@ 24" from the Hitch end)
Remote Valves	2 Pairs (Front), 2 pairs (Rear)

Dimension

Overall length (Frame to Link, in.)	135
Overall width with tires (in.)	72.6
Wheelbase (in.)	83.1
Height to top (in.)	105.4

Tire Size

Ag Front / Rear	9.5 - 24 / 16.9 - 28
IND Front / Rear	10.5/80×18 10PR / 19.5Lx24 8PR
Large Ag Front / Rear	11.2-24 / 16.9-30
R14 Front / Rear	320-85R20 119D / 420/75R34 142D

Weight

Total weight without ballast (lbs.)	5,886
-------------------------------------	-------
