



## Ironcraft 2515 - Medium-Duty 15' Flex-Wing Cutters

[Read More](#)

**SKU:** 2515

**Categories:** [Ironcraft](#)

### Product Description

## Ironcraft 2515 - Medium-Duty 15' Flex-Wing Cutters

Utilizing a smooth-top deck and spring suspension, the 2515 will make quick work of tough jobs. Designed for use with tractors with a 50 horsepower minimum, this medium-duty Flex-Wing requires only one hydraulic remote. For its 180" cut width, the cutter uses three spindles with two free-swinging blades each, which reduce the shock of impact when a stationary object is contacted. Slip clutches protect the gearboxes and drivelines from damage. Standard equipment includes driveline shields, clutch shields, chain discharge shields and a safety tow chain.

|                   |                                         |
|-------------------|-----------------------------------------|
| Product Family    | 2515 Series                             |
| Product           | 2515                                    |
| Description       | 15' Medium Duty Flex Wing Rotary Cutter |
| RPM               | 540 or 1000                             |
| HP Required       | 50 minimum PTO                          |
| Working Width     | 180"                                    |
| Overall Width     | 188"                                    |
| Overall Length    | 186"                                    |
| Transport Width   | 90"                                     |
| Transport Height  | 83" - 87"                               |
| Tongue Weight     | 1500 lbs                                |
| Weight (lbs)      | 4500 lbs. w/ 6-26" laminated tires      |
| Cutting Height    | 2" to 15"                               |
| Cutting Capacity  | 2.5"                                    |
| Deck Thickness    | 10 GA                                   |
| Height Adjustment | Hydraulic Cylinder                      |
| Wing Adjustments  | Heavy Duty Turnbuckle                   |

|                         |                                                       |
|-------------------------|-------------------------------------------------------|
| Jack Stand              | Standard                                              |
| Side Bands              | 1/4" x 13-1/2"                                        |
| Suspension              | 1 Heavy Duty Spring                                   |
| Skid Shoes              | Replaceable                                           |
| PTO Drive Shaft         | ASAE CAT 6                                            |
| Wing Drive PTO          | ASAE CAT 4                                            |
| Driveline Protection    | Slip Clutch                                           |
| Blade Holder            | Round Pan                                             |
| Gearbox Rating          | 235 HP                                                |
| Outboard Gearbox Rating | 190 HP                                                |
| Wing Flex               | 22 Degrees Down to 88 Degrees Up                      |
| Wing Free Float         | 22 Degrees Down to 45 Degrees Up                      |
| Blades                  | 1/2" x 4" Uplift                                      |
| Blade Overlap           | 6"                                                    |
| Output Shaft Diameter   | 2"                                                    |
| Wheel Type              | 20" or 26" Laminated and 27" Foam Filled or Pneumatic |
| Hitch Type              | Swivel Pivot Self Leveling                            |
| Gearbox Warranty        | 5 year limited                                        |
| Safety Tow Chain        | Standard                                              |
| Guarding Options        | Single Row Chains Standard                            |
| FPM                     | 17135                                                 |

---